

## **Declaration of Performance**

In accordance to CPR 305/2011:

- 1. Identification of product type: Tubular cored electrode welding consumable Brand name: Hobart<sup>®</sup> Fabshield<sup>®</sup> 91T8 Part numbers and diameters: S229325 (2.0mm) Classification: EN ISO 18276-A T55 4 Z Z NO 1 H10 2. Batch number identifying the Refer to product label construction product: 3. Intended use of the construction Metallic structures or composite metal and product: concrete structures 4. Name and contact address of Hobart Brothers LLC 101 Trade Square East the manufacturer: Troy, OH 45373 USA 5. Authorized representative: N/A 6. System of assessment and System 2+ verification of constancy of performance of the construction product: TÜV Rheinland/0035 performed: 7. Notified body/Reg. No: • Initial inspection of the manufacturing plant and of factory production control Continuous surveillance, assessment, • and evaluation of factory production control under System 2+ and issued certificate of conformity of the factory production control no. 0035-CPR-C810 8. European Technical N/A
- 9. Declared performance (see chart on the right):

Assessment:

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer by:

David A. Thomas - Quality Assurance Representative Troy, OH USA 11/12/19

|                               |              |      |        | DOP No. 24                                |
|-------------------------------|--------------|------|--------|---|
| Essential<br>Characteristics: | Performance: |      |        | Harmonized<br>Technical<br>Specification: |
|                               | Min          | Max  | Values |   |
| Chemical composition:         |              |      |        |   |
| C:                            | -            | -    | %      |   |
| Mn:                           | 0.5          | -    | %      | EN 13479:2017                             |
| Si:                           | -            | 1.0  | %      |   |
| P:                            | -            | 0.03 | %      |   |
| S:                            | -            | 0.03 | %      |   |
| Cr:                           | 0.3          | -    | %      |   |
| Ni:                           | 0.5          | -    | %      |   |
| Mo:                           | 0.2          | -    | %      |   |
| V:                            | 0.1          | -    | %      |   |
| Nb:                           | -            | -    | %      |   |
| AI:                           | -            | 1.8  | %      | ]   |
| Cu:                           | -            | -    | %      |   |